# Mounting accessories for cylinders

Mountings in aluminium for cylinders ISO 15552

## Main features

32 ÷ 320 ISO CMS..ALIS+V

Bores Ø MP6 Type







## Technical data

| Type | Description | Material | Treatment |
|---|---|---|---|
| CMS..ALIS+V | Mounting for cylinders in aluminium. Narrow rear eye with spherical bearing DIN 648K. Supplied with screws. | Die-cast aluminium | Sifting |

## Dimensions

| For cylinder Ø mm | Code | Item | A | B | C | D | EN | ER | F | G | E | L | M | N | P | H | R | S | Z | T | XD | Weight (g) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 32 | 042101 | CMS032ALIS+V | 32,5 | 10,5 | 22 | 10 | 14 | 16 | 30 | 9 | 6,6 | 45 | 11 | 5,5 | 5 | - | - | 4 | 32,5 | 6,25 | 142 | - |
| 40 | 042102 | CMS040ALIS+V | 38 | 12 | 25 | 12 | 16 | 19 | 35 | 9 | 6,6 | 52 | 11 | 5,5 | 5 | - | - | 6 | 39 | 7 | 160 | - |
| 50 | 042103 | CMS050ALIS+V | 46,5 | 15 | 27 | 16 | 21 | 21 | 40 | 11 | 9 | 65 | 15 | 6,5 | 5 | 51 | 18 | 8 | 47 | 9,25 | 170 | - |
| 63 | 042104 | CMS063ALIS+V | 56,5 | 15 | 32 | 16 | 21 | 24 | 45 | 11 | 9 | 75 | 15 | 6,5 | 5 | - | - | 8 | 52 | 9,25 | 190 | - |
| 80 | 042105 | CMS080ALIS+V | 72 | 18 | 36 | 20 | 25 | 28,5 | 45 | 14 | 11 | 95 | 18 | 10 | 5 | 72 | 24 | 10 | 67 | 11,5 | 210 | - |
| 100 | 042106 | CMS100ALIS+V | 89 | 18 | 41 | 20 | 25 | 30 | 55 | 14 | 11 | 115 | 18 | 10 | 5 | - | - | 10 | 77 | 13 | 230 | - |
| 125 | 042107 | CMS125ALIS+V | 110 | 25 | 50 | 30 | 37 | 40 | 60 | 20 | 13,5 | 140 | 20 | 10 | 7 | - | - | 13 | 98 | 15 | 275 | - |
| 160 | 042108 | CMS160ALIS+V | 140 | 28 | 55 | 35 | 43 | 45 | 65 | 20 | 18 | 180 | 26 | 10 | 7 | - | - | 14 | 130 | 20 | 315 | - |
| 200 | 042109 | CMS200ALIS+V | 175 | 28 | 60 | 35 | 43 | 48 | 75 | 25 | 18 | 220 | 26 | 11 | 7 | - | - | 14 | 155 | 22,5 | 335 | - |
| 250 | 042160 | CMS250ALIS+V | 220 | 33 | 70 | 40 | 49 | 52 | 90 | 25 | 22 | 270 | 33 | 11 | 11 | - | - | 19 | 205 | 25 | 375 | - |
| 320 | 040197 | CMS320ALIS+V | 270 | 45 | 80 | 50 | 60 | 63 | 110 | 30 | 22 | 350 | 33 | 11 | 11 | - | - | - | - | 28 | 420 | - |

## Main features

32 ÷ 200 ISO FLV..ALIS+V

Bores Ø VDMA MF1/MF2 Type







## Technical data

| Type | Description | Material | Treatment |
|---|---|---|---|
| FLV..ALIS+V | Mounting for cylinders in aluminium. Flange. For front or rear mounting. Supplied with screws. | Die-cast aluminium | Anodizing |

## Dimensions

| For cylinder Ø mm | Code | Item | A | ØAP | AO | R | AS | AR | AQ | AT | AV | C | D | ZF | W | Weight (g) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 32 | 042150 | FLV032ALIS+V | 32,5 | 7 | 30 | 6,5 | 10 | 45 | 32 | 64 | 86 | 10,5 | 5 | 130 | 16 | - |
| 40 | 042151 | FLV040ALIS+V | 38 | 9 | 35 | 6,5 | 10 | 52 | 36 | 72 | 96 | 11 | 5 | 145 | 20 | - |
| 50 | 042152 | FLV050ALIS+V | 46,5 | 9 | 40 | 9 | 12 | 65 | 45 | 90 | 115 | 15 | 5,5 | 155 | 25 | - |
| 63 | 042153 | FLV063ALIS+V | 56,5 | 9 | 45 | 9 | 12 | 75 | 50 | 100 | 130 | 15 | 5,5 | 170 | 25 | - |
| 80 | 042154 | FLV080ALIS+V | 72 | 12 | 45 | 11 | 16 | 95 | 63 | 126 | 165 | 18 | 7 | 190 | 30 | - |
| 100 | 042155 | FLV100ALIS+V | 89 | 14 | 55 | 11 | 16 | 115 | 75 | 150 | 187 | 18 | 7 | 205 | 35 | - |
| 125 | 042156 | FLV125ALIS+V | 110 | 16 | 60 | 13 | 20 | 140 | 90 | 180 | 224 | 19 | 9,5 | 245 | 45 | - |
| 160 | 042157 | FLV160ALIS+V | 140 | 18 | 65 | 17 | 20 | 180 | 115 | 230 | 280 | 25 | 10,5 | 280 | 60 | - |
| 200 | 042158 | FLV200ALIS+V | 175 | 22 | 75 | 17 | 25 | 220 | 135 | 270 | 320 | 25 | 12,5 | 300 | 70 | - |