## FLEXBIMEC

## **AUTOMATIC REWIND, SPRING - DRIVEN HOSE REELS**

Standard series

Ø max 1/2" - up to 20 m length Ø max 3/8" - up to 25 m length

Automatic rewind, spring-driven hose reel, **standard series**, in painted steel or in stainless steel AISI 304, suitable for hoses of max 20 m length (ø hose 1/2") or max 25 m length (ø hose 3/8").

The wetted parts of the painted steel models on demand can also be replaced by stainless steel parts (see pages 217 – 218).

The hose reel is supplied without hoses and can be used with hoses for the supply of oils, antifreeze, grease, compressed air and water. Please see catalogue pages 220 and 221 for the selection of the required hoses.

On demand the hose reels can also be supplied with a **spring brake kit** (see information at the end of this page!); please add suffix "/HB" to the article number (f. ex. 9016/HB)!













Art.no. **9767** Art.no. **9768** 



Art.no. **9760** Art.no. **9765** 



Art.no.	Material	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose	Suitable pivoting wall bracket	Included swivel joint	Dimensions (A-B-C) (mm)	Spool width (D)	Weight
9016	Painted steel	600 bar	- 1/2" (M) - 1/2" (F)	10 mm	1/2″	15 m	9767	9951	215x570x430	120 mm	14 Kg
9021					1/2"	20 m	9768		245x570x430	150 mm	18 Kg
9022					3/8"	25 m	9768				19 Kg
9517	Stainless steel AISI 304	200 bar			1/2"	15 m	9760	9963	215x570x430	120 mm	14 Kg
9521					3/8"	25 m	9765		245x570x430	150 mm	19 Kg
9522					1/2"	20 m	9765				18 Kg



## OPTIONAL

## /HB Hydraulic spring brake kit (patented)

Safety device for the controlled rewind of hoses, installable on all spring-driven hose reel models, eliminating the dangers caused by an uncontrolled rewind or a sudden release of the hose when unwinded during its use.







