



► Ordering Information

	Order No.	Cap. (tons)	Jaw Type	Max.		Jaw		Screw Size (in.)	Weight (kg)
				Reach (mm)	Spread (mm)	Thickness (mm)	Width (mm)		
	1020	1	2-Jaw	54,0	82,6	3,6	6,4	5/16 - 24 x 98,4 mm	0,14
	1021		3-Jaw	54,0	82,6				
	1022	2	2-Jaw *	82,6	101,6	Upper 4,8 Lower 3,2	Upper 6,4 Lower 12,7	3/8 - 24 x 124 mm	0,40
	1023		2/3-Jaw *	85,7	120,7				
	1024	5	2/3-Jaw *	82,6	152,4	Upper 23,8 Lower 6,4	Upper 9,5 Lower 19,1	9/16 - 20 x 178 mm	0,43
	1026		2/3-Jaw *	82,6	177,8				
	1025	5	Long 2-Jaw *	139,7	152,4	Upper 23,8 Lower 6,4	Upper 9,5 Lower 19,1	9/16 - 20 x 178 mm	0,19
	1027		Long 2/3-Jaw *	139,7	177,8				1,65
	1035	7	2-Jaw *	127,0	228,6	Upper 7,9 Lower 8,7	Upper 25,4 Lower 25,4	11/16 - 18 x 229 mm	2,04
	1037		2/3-Jaw *	127,0	266,7				2,78
	1036	7	Long 2-Jaw	222,3	241,3	8,7	25,4	11/16 - 18 x 229 mm	2,44
	1038		Long 2/3-Jaw	222,3	279,4				3,69
	1039	13	2-Jaw	279,4	304,8	14,3	25,4	13/16 - 16 x 305 mm	4,90
	1040		Long 2-Jaw	387,4	393,7				5,90
	1041		2/3-Jaw	279,4	304,8				7,37
	1042		Long 2/3-Jaw	387,4	431,8				8,50
	1043	17.5	Long 2-Jaw	368,3	355,6	20,6	32,5	1 - 14 x 343 mm	10,43
	1044		Long 2-Jaw	476,3	406,4				11,79
	1045		3-Jaw	368,3	355,6				14,97
	1046		Long 3-Jaw	476,3	406,4				16,78
	1048	25	Long 2-Jaw	565,2	508,0	27,0	38,1	1 1/4 - 12 x 422 mm	19,39
	1050		Long 3-Jaw	565,2	508,0				27,22

* Reversible Jaws