



P16AP

PORTABILITY FOR SERVICE

Finn-Power P16AP is air pump operated hydraulic crimping machine for repair workshops and field use. Easy to use, light and compact in size, allowing to be carried to any location.

Available also with hand pump (HP-model) and separate head/power pack configuration (Z-model).

TECHNICAL DATA


Max crimping dia (mm) ¹⁾	45
Max crimping dia (inch) ¹⁾	1.77
Max crimping force (kN)	955
Max crimping force (tonnage)	95
Hose size ID (inch)	1 *
Die set series	16
Max opening (mm) ²⁾	+20
Max opening without dies (mm)	59
Master die D/L (mm)	39/64
Master die D/L (inch)	1.54/2.52
Motor Power	Air pressure

DIMENSIONS (LxWxH)

(mm)	331x346x271
(inch)	13.1x13.6x15.4

WEIGHT (KG/LBS)

28/62



- 1) With standard dies. Crimping range can be increased with special dies.
- 2) Maximum opening is the total die travel. Add this value to the minimum crimping diameter of the die set used. The result is the maximum opening of the machine with die set in place.

CONTROL

Manual

MODELS

Z-model



DIE SET 16-SERIES

DieSetNo	D (mm)	L (mm)	Crimp. range (mm)
18212/10	10	55	10.0-12.0
18212/12	12	55	12.0-14.0
18212/14	14	55	14.0-16.0
18212/16	16	55	16.0-19.0
18212/19	19	55	19.0-23.0
18212/23	23	55	23.0-27.0
18212/27	27	65	27.0-31.0
18212/31	31	65	31.0-38.0

In addition to the standard die sets, a wide range of special die sets is available on request.

* ACCORDING TO THE FITTING.

FURTHER INFO ON PRODUCTS,
PLEASE REVERT TO SPECIFIC PRODUCT CARD

FINNPOWER.FI

LILLBACKAUSA.COM