

Model Shown:
SK25T



NOTE: Storage cases are not included with the 25 ton startup kits, they must be ordered separately.

Features


THE RIGHT CHOICE FOR THOSE HIGHER TON MAINTENANCE KIT NEEDS.

- 25 Ton Start-Up Kit covers a range of lifting, shifting, and positioning needs
- Broad range of cylinder types and strokes to fit many applications
- SK25TE kit is CE Compliant



Optional 25 Ton Storage Cases

MB5



308435OR9



Order No.	Description
MB5	Metal Box Construction, 813 mm (L) x 483 mm (W) x 356 mm (H)
308435OR9	Wooden Box Construction, 914 mm (L) x 445 mm (W) x 356 mm (H)

Ordering Information

Kit Contents - Order no: SK25TE			
Hand Pump	Usable Oil Cap. (l)	Volume Per Stroke Low / High Press. (l)	Weight (kg)
P59L	1082	12 / 2,6	4,1
Gauge	Type	Primary Units	Face Diameter (mm)
9040E	analog	bar	63,5
Hose	Length (m)	Burst Rating	I.D. (mm)
9754E	1,8	4:1	6,5
Cylinders	Capacity* Short Tons	Stroke (mm)	Collapsed Height (mm)
C256C	22,7	158,8	273,0
RSS302	27,2	61,9	117,5
RH302	27,2	63,5	158,8
RLS300	27,2	12,7	58,7
Spreader	Min. Clearance (mm)	Max Spread (mm)	Weight (kg)
HS2000	14,2	101,6	2,2

* Values shown in short tons (2,000 lb). To convert to long tons, multiply by 0.893. To convert to metric tons, multiply by 0.907.